

離脱防止押輪 ワイド型 CMB

- 1、爪の形状をワイドにし押しボルト数を少なくする事で施工性を向上
- 2、ワイドな爪は水圧により管体が離脱方向に動いても一定深さ以上食い込まない
- 3、ダクタイル鋳鉄管の内面モルタルライニングには悪影響を与えません




(単位:円)

呼び径	本体	付属品価格							酸化被膜 組価格	合金 組価格	SUS304 組価格	呼び径
		T頭ボルト・ナット						Kゴム輪				
		酸化被膜		合金		SUS304						
		単価	価格	単価	価格	単価	価格					
75	6,790	430	1,720	650	2,600	2,220	8,880	1,760	10,270	11,150	17,430	75
100	7,890	510	2,040	730	2,920	3,140	12,560	1,970	11,900	12,780	22,420	100
150	12,670	510	3,060	730	4,380	3,140	18,840	2,750	18,480	19,800	34,260	150
200	13,750	510	3,060	730	4,380	3,140	18,840	3,430	20,240	21,560	36,020	200
250	19,070	510	4,080	730	5,840	3,140	25,120	4,420	27,570	29,330	48,610	250
300	21,130	580	4,640	840	6,720	3,180	25,440	7,830	33,600	35,680	54,400	300
350	33,500	580	5,800	840	8,400	3,180	31,800	9,560	48,860	51,460	74,860	350
400	44,920	650	7,800	950	11,400	3,270	39,240	10,690	63,410	67,010	94,850	400
450	51,930	650	7,800	950	11,400	3,270	39,240	11,570	71,300	74,900	102,740	450
500	59,370	650	9,100	950	13,300	3,270	45,780	12,060	80,530	84,730	117,210	500
600	71,490	690	9,660	1,050	14,700	3,370	47,180	12,890	94,040	99,080	131,560	600
700	133,360	1,100	17,600	1,490	23,840	6,020	96,320	17,750	168,710	174,950	247,430	700
800	176,690	1,100	22,000	1,490	29,800	6,020	120,400	21,810	220,500	228,300	318,900	800

※ 同芯ゴム輪K形を用いれば、現場で簡単に芯出しができます(φ75～700)。

(mm)



呼び径	F	B	①押しボルト	②T頭ボルト	重量 (kg)		呼び径
					本体のみ	組 酸化被膜	
75	258	60	2-M20×51	4 -M16× 85	2.38	3.49	75
100	295		2-M20×55	4 -M20× 90	2.64	4.48	100
150	346		3-M20×55	6 -M20× 90	4.38	7.11	150
200	402				5.41	8.24	200
250	454	61	4-M20×55	8 -M20× 90	6.88	10.60	250
300	505			8 -M20× 100	9.16	13.27	300
350	556	62	5-M20×55	10 -M20× 100	11.70	16.77	350
400	606	66	6-M20×48	12 -M20× 110	16.44	22.82	400
450	657	71			18.34	24.84	450
500	708		7-M20×48	14 -M20× 110	22.38	29.90	500
600	811	72		14 -M20× 120	30.58	38.47	600
700	941	85	8-M22×60	16 -M24× 120	47.10	60.96	700
800	1044	88	10-M22×60	20 -M24× 120	58.90	75.92	800