

離脱防止押輪 ワイド型 CMB

- 1、爪の形状をワイドにし押しボルト数を少なくする事で施工性を向上
- 2、ワイドな爪は水圧により管体が離脱方向に動いても一定深さ以上食い込まない
- 3、ダクタイル鋳鉄管の内面モルタルライニングには悪影響を与えません




(単位:円)

呼び径	本体	付属品価格							Kゴム輪	酸化被膜 組価格	合金 組価格	SUS304 組価格	呼び径
		T頭ボルト・ナット											
		酸化被膜		合金		SUS304							
		単価	価格	単価	価格	単価	価格						
75	6,170	390	1,560	590	2,360	2,020	8,080	1,600	9,330	10,130	15,850	75	
100	7,170	460	1,840	660	2,640	2,850	11,400	1,790	10,800	11,600	20,360	100	
150	11,520	460	2,760	660	3,960	2,850	17,100	2,500	16,780	17,980	31,120	150	
200	12,500	460	2,760	660	3,960	2,850	17,100	3,120	18,380	19,580	32,720	200	
250	17,340	460	3,680	660	5,280	2,850	22,800	4,020	25,040	26,640	44,160	250	
300	19,210	530	4,240	760	6,080	2,890	23,120	7,120	30,570	32,410	49,450	300	
350	30,450	530	5,300	760	7,600	2,890	28,900	8,690	44,440	46,740	68,040	350	
400	40,840	590	7,080	860	10,320	2,970	35,640	9,720	57,640	60,880	86,200	400	
450	47,210	590	7,080	860	10,320	2,970	35,640	10,520	64,810	68,050	93,370	450	
500	53,970	590	8,260	860	12,040	2,970	41,580	10,960	73,190	76,970	106,510	500	
600	64,990	630	8,820	950	13,300	3,060	42,840	11,720	85,530	90,010	119,550	600	
700	121,240	1,000	16,000	1,350	21,600	5,470	87,520	16,140	153,380	158,980	224,900	700	
800	160,630	1,000	20,000	1,350	27,000	5,470	109,400	19,830	200,460	207,460	289,860	800	

※ 同芯ゴム輪K形を用いれば、現場で簡単に芯出しができます(φ75~700)。

(mm)



呼び径	F	B	①押しボルト	②T頭ボルト	重量(kg)		呼び径
					本体のみ	組酸化被膜	
75	258	60	2-M20×51	4 -M16× 85	2.38	3.49	75
100	295		2-M20×55	4 -M20× 90	2.64	4.48	100
150	346		3-M20×55	6 -M20× 90	4.38	7.11	150
200	402				5.41	8.24	200
250	454	61	4-M20×55	8 -M20× 90	6.88	10.60	250
300	505			8 -M20× 100	9.16	13.27	300
350	556	62	5-M20×55	10 -M20× 100	11.70	16.77	350
400	606	66	6-M20×48	12 -M20× 110	16.44	22.82	400
450	657				18.34	24.84	450
500	708	71	7-M20×48	14 -M20× 110	22.38	29.90	500
600	811				14 -M20× 120	30.58	38.47
700	941	85	8-M22×60	16 -M24× 120	47.10	60.96	700
800	1044	88	10-M22×60	20 -M24× 120	58.90	75.92	800