

離脱防止押輪 ワイド型 CMB

- 1、爪の形状をワイドにし押しボルト数を少なくする事で施工性を向上
- 2、ワイドな爪は水圧により管体が離脱方向に動いても一定深さ以上食い込まない
- 3、ダクタイル鋳鉄管の内面モルタルライニングには悪影響を与えません




(単位:円)

呼び径	本体	付属品価格						Kゴム輪	酸化被膜 組価格	合金 組価格	SUS304 組価格	呼び径
		T頭ボルト・ナット										
		酸化被膜		合金		SUS304						
		単価	価格	単価	価格	単価	価格					
75	4,880	260	1,040	390	1,560	1,600	6,400	1,230	7,150	7,670	12,510	75
100	5,670	350	1,400	520	2,080	2,250	9,000	1,400	8,470	9,150	16,070	100
150	9,100	350	2,100	520	3,120	2,250	13,500	1,940	13,140	14,160	24,540	150
200	9,880	350	2,100	520	3,120	2,250	13,500	2,430	14,410	15,430	25,810	200
250	13,700	350	2,800	520	4,160	2,250	18,000	3,150	19,650	21,010	34,850	250
300	15,180	410	3,280	600	4,800	2,290	18,320	5,570	24,030	25,550	39,070	300
350	23,410	410	4,100	600	6,000	2,290	22,900	6,840	34,350	36,250	53,150	350
400	31,970	440	5,280	680	8,160	2,350	28,200	7,660	44,910	47,790	67,830	400
450	36,280	440	5,280	680	8,160	2,350	28,200	8,220	49,780	52,660	72,700	450
500	41,480	440	6,160	680	9,520	2,350	32,900	8,630	56,270	59,630	83,010	500
600	51,370	470	6,580	750	10,500	2,420	33,880	9,200	67,150	71,070	94,450	600
700	95,840	780	12,480	1,060	16,960	4,320	69,120	12,660	120,980	125,460	177,620	700
800	126,980	780	15,600	1,060	21,200	4,320	86,400	15,660	158,240	163,840	229,040	800

※ 同芯ゴム輪K形を用いれば、現場で簡単に芯出しができます(φ75~700)。

(mm)



呼び径	F	B	①押しボルト	②T頭ボルト	重量(kg)		呼び径
					本体のみ	組 酸化被膜	
75	258	60	2-M20×51	4 -M16× 85	2.38	3.49	75
100	295		2-M20×55	4 -M20× 90	2.64	4.48	100
150	346		3-M20×55	6 -M20× 90	4.38	7.11	150
200	402				5.41	8.24	200
250	454	61	4-M20×55	8 -M20× 90	6.88	10.60	250
300	505		8 -M20× 100	9.16	13.27	300	
350	556	62	5-M20×55	10 -M20× 100	11.70	16.77	350
400	606	66	6-M20×48	12 -M20× 110	16.44	22.82	400
450	657	71			18.34	24.84	450
500	708		7-M20×48	14 -M20× 110	22.38	29.90	500
600	811	14 -M20× 120		30.58	38.47	600	
700	941	85	8-M22×60	16 -M24× 120	47.10	60.96	700
800	1044	88	10-M22×60	20 -M24× 120	58.90	75.92	800